



Adesso Edge II Back to Wall Toilet Suite

Product Disclosure Information Self-Assessment

Version: V1

Product name	Adesso Edge II Back to Wall Toilet Suite	
Product line	Adesso Edge II Toilet Suites	
Product identifier	(7)734555 (7)734600	

Product description

White Vitreous China finish. Soft close, quick release seat. Recommended for domestic, hotel and commercial use. Hygiene Flush Rimless Pan. WDI inlet valve. Universal back or bottom entry. WELS Rating 4 3.5L per average flush Adjustable set out from 65mm – 175mm Optional - Vario trap 145–250mm

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene - G1.3.2

Contributions to compliance

- B2. Product has a 5-year warranty.
- G1. Pans intended for use with flushing cisterns and other flushing devices complying with AS 1172.2.
- G1. WELS standard (AS/NZS 6400:2016 Water efficient products, Wels Certificate # L05301

Scope of use

The Adesso Edge II toilet is intended for use in domestic bathrooms. It is suitable for hot and cold water use, and with mains pressure systems The unit is floor mounted with either an S trap or P trap configuration. The system is compatible with all fittings manufactured to NZS 3501

Conditions of use

The Adesso Edge II suite must be installed by a registered plumber in accordance with the productspecification sheet and the NZBC. This product is intended for domestic use only. It can ve specified for high use applications such as public amenities, schools, sports facilities, factories, or commercial premises etc. This product is cleanable and impervious to moisture — cleaning shall be done in accordance with the manufacturer's cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Adesso Edge II Specification		https://adesso.co.nz/bathroom/toilets/back-to-wall-suite/edge-back-to-wall-toilet-suite-rimless-with-standard-seat

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	XIAMEN BESTBATH CERAMICS CO
Legal and trading name of importer	MICO NEW ZEALAND LIMITED
Importer address for service	Unit3/1 Show Place Christchurch 8024
Importer website	www.mico.co.nz
Importer NZBN	9429040952543
Importer email	info@mico.co.nz
Importer phone number	033381009

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Sanitary fixtures and appliances

	Yes	No
Suitable for Accessible facilities		×
Provision of hot water		×

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c) 5 years if:
 - i. the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
 - ii. failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate sanitation,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.