

# Adesso Form toilet

## BPIR Declaration

Version:

**Designated building product:** Class 1

### Declaration

Robertson NZ Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

### Product/system

<b>Name</b>	Adesso Form toilet
<b>Line</b>	Toilet Suite
<b>Identifier</b>	(7)729193

### Description

Vitreous China Back to wall toilet Suite with dual flush. Soft close quick release seat. WELS 4 star. 3.5L average flush. Back and Bottom entry. S trap set out 55 - 265mm. P trap set out 180mm

### Scope of use

Adesso Form Toilet Suite is intended for Domestic bathrooms.

### Conditions of use

Adesso Form Toilet Suites must be installed by a registered plumber registered plumber. Cleaning shall be done in accordance with the manufacturers cleaning instructions.

### Relevant building code clauses

**B2 Durability** — B2.3.1 (c)

**F2 Hazardous building materials** — F2.3.1

**G1 Personal Hygiene** — G1.3.2

**G12 Water Supplies** — G12.3.2

## H1 Energy efficiency — H1.3.3

### Contributions to compliance

Product has a 5 year Warranty.

### Supporting documentation

The following additional documentation supports the above statements:

None added

For further information supporting Adesso Form toilet claims refer to our website.

### Contact details

<b>Manufacture location</b>	Overseas
<b>Legal and trading name of manufacturer</b>	Robertson NZ Limited
<b>Legal and trading name of importer</b>	Robertson NZ Limited
<b>Importer address for service</b>	25 Vestey Dr Auckland 1060
<b>Importer website</b>	<a href="http://www.robertson.co.nz">www.robertson.co.nz</a>
<b>Importer NZBN</b>	9429032734980
<b>Importer email</b>	info@robertson.co.nz
<b>Importer phone number</b>	09 573 0490

## Appendix

Note: The below appendix includes information relating to BPIR Ready.

Publishing this information is not a requirement under BPIR. Its inclusion here is to provide a reference for how this BPIR summary was generated as well as to help summary creators understand the performance clauses suggested by BPIR Ready.

### BPIR Ready selections

**Category:** Toilets and urinals

	<b>Yes</b>	<b>No</b>
Suitable for Accessible facilities		x
Provision of hot water		x
Intended for hot water transmission	x	
Capable of being permanently concealed		x
Suitable for accessible facilities		x

## **Building code performance clauses**

### **B2 Durability**

#### **B2.3.1**

*Building elements* must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (c) 5 years if: the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### **F2 Hazardous building materials**

#### **F2.3.1**

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### **G1 Personal Hygiene**

#### **G1.3.2**

*Sanitary fixtures* shall be located, constructed and installed to:

- a. facilitate *sanitation*,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

### **G12 Water Supplies**

### G12.3.2

A potable *water supply system* must be—

- a. protected from contamination; and
- b. installed in a manner that avoids the likelihood of contamination within the system and the water main; and
- c. installed using components that will not contaminate the water.

## **H1 Energy efficiency**

### H1.3.3

Account must be taken of physical conditions likely to affect energy performance of buildings, including

- a. the thermal mass of *building elements*; and
- b. the building orientation and shape; and
- c. the airtightness of the building envelope; and
- d. the heat gains from services, processes and occupants; and
- e. the local climate; and
- f. heat gains from solar radiation.