

Class 1

# Raymor Boston Bath

Product Disclosure Information Self-Assessment

Version: V1

<b>Product name</b>	Raymor Boston Bath
<b>Product line</b>	
<b>Product identifier</b>	(7)696978

## Product description

Raymor Boston Baths are made from a one-piece bath 100% acrylic board, reinforced by FRP.

Size: W 1700 x H 750 x D 430mm

Colour: White

Volume: 215L

Weight: 23Kg

## Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.5

## Contributions to compliance

- B2 Durability. B2.3.1 Raymor baths carry a 5 year warranty for normal, domestic use.
- F2 Hazardous building materials o F2.3.1 Raymor baths are safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.
- G1 Personal Hygiene o G1.3.2 Raymor baths shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13

First party self-assessment generated Aug 21, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=7861fd802b76a4fadef9a3b11502e3618bbde89d>

Get BPIR Ready | [bpir.nz](https://bpir.nz)

Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-water-borne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users.

•G12 For Water supplies G12, the prime building product objective is to ensure that the product used in water supply will not contaminate potable water either by way of material leaching into the water or cross connections and will not leak.

## Scope of use

Raymor baths are intended for normal, domestic use only. They are designed to enclose water. They can be used with water temperatures up to 55 degrees Celsius.

These Raymor are to be installed using the waste fitting supplied separately.

They baths are to be mounted on a flat surface inside a structure to support the bath.

## Conditions of use

Raymor baths must be installed in accordance with the instructions provided. We recommend these baths are installed by an authorised installer. Floor surfaces must be flat and free of movement, and unheated. These products are intended for normal, domestic use only. They are cleanable and impervious to moisture — cleaning of these baths shall be done in accordance with the manufacturer's cleaning instructions.

## Supporting documentation

The following additional documentation supports the above statements:

None added

## Contact details

<b>Manufacture location</b>	Overseas
<b>Legal and trading name of manufacturer</b>	NINGBO WALTMAL SANITARY WARES CO
<b>Legal and trading name of importer</b>	MICO NEW ZEALAND LIMITED
<b>Importer address for service</b>	Unit 3/1 Show Place Christchurch 8024
<b>Importer website</b>	www.mico.co.nz
<b>Importer NZBN</b>	9429040952543
<b>Importer email</b>	info@mico.co.nz
<b>Importer phone number</b>	033381009

First party self-assessment generated Aug 21, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=7861fd802b76a4fedef9a3b11502e3618bbde89d>

Get BPIR Ready | [bpir.nz](https://bpir.nz)

## Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

---

## Appendix

### BPIR Ready selections

Category: Sanitary fixtures and appliances

	Yes	No
Suitable for Accessible facilities		x
Provision of hot water	x	

### Building code performance clauses

All relevant building code performance clauses listed in this document:

#### B2 Durability

##### B2.3.1

*Building elements* must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (c) 5 years if:
- the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
  - failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

#### F2 Hazardous building materials

##### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G1 Personal Hygiene

##### G1.3.2

*Sanitary fixtures* shall be located, constructed and installed to:

- facilitate *sanitation*,
- avoid risk of food contamination,
- avoid harbouring dirt or germs,
- provide appropriate privacy,

First party self-assessment generated Aug 21, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=7861fd802b76a4faded9a3b11502e3618bbde89d>

Get BPIR Ready | [bpir.nz](https://bpir.nz)

- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

## G12 Water Supplies

### G12.3.5

*Sanitary fixtures and sanitary appliances* must be provided with hot water when intended to be used for

- a. utensil washing; and
- b. personal washing, showering, or bathing.