

Raymor Coral Basins

BPIR Declaration

Version: V1

Designated building product: Class 1

Declaration

MICO NEW ZEALAND LIMITED has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

| | |
|-------------------|---------------------|
| Name | Raymor Coral Basins |
| Line | Raymor Basins |
| Identifier | (7)781548 |

Description

Raymor Coral Basins are made from vitreous china, with one tap hole configuration and a chrome electro-plated plastic overflow ring.

Size: W 450mm, L 365mm, H 180mm

Colour: White

Scope of use

Raymor basins are intended for normal, domestic use only. They are designed to enclose water with a separate waste to allow drainage of water. They can be used with water temperatures up to 55 degrees Celsius.

These Raymor basins are to be installed using the waste fitting supplied separately.

The basins are to be mounted on a flat wall surface.

Conditions of use

Raymor basins must be installed in accordance with the instructions provided. We recommend these basins are installed by an authorised installer or plumber. These products are intended for normal, domestic use only. They are cleanable and impervious to moisture – cleaning of these basins shall be done in accordance with the manufacturer's cleaning instructions.

Relevant building code clauses

B2 Durability – B2.3.1 (c)

F2 Hazardous building materials – F2.3.1

G1 Personal Hygiene – G1.3.2

G12 Water Supplies – G12.3.5

Contributions to compliance

- B2 Durability. B2.3.1 Raymor basins carry a 5-year warranty for normal, domestic use.
- F2 Hazardous building material. F2.3.1 Raymor basins are safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.
- G1 Personal Hygiene. G1.3.2 Raymor basins shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-waterborne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users.
- G12 For Water supplies G12, the prime building product objective is to ensure that the product used in water supply will not contaminate potable water either by way of material leaching into the water or cross connections and will not leak.

Supporting documentation

The following additional documentation supports the above statements:

None added

For further information supporting Raymor Coral Basins claims refer to our website.

Contact details

| | |
|--|--|
| Manufacture location | Overseas |
| Legal and trading name of manufacturer | XIAMEN BESTBATH CERAMICS CO |
| Legal and trading name of importer | MICO NEW ZEALAND LIMITED |
| Importer address for service | Unit 3/1 Show Place Christchurch 8024 |
| Importer website | www.mico.co.nz |
| Importer NZBN | 9429040952543 |
| Importer email | info@mico.co.nz |
| Importer phone number | 033381009 |

Raymor Coral Basins are not subject to a warning or ban under [s26 of the Building Act](#).

Appendix

Note: The below appendix includes information relating to BPIR Ready.

Publishing this information is not a requirement under BPIR. Its inclusion here is to provide a reference for how this BPIR summary was generated as well as to help summary creators understand the performance clauses suggested by BPIR Ready.

BPIR Ready selections

Category: Sanitary fixtures and appliances [legacy category]

| | Yes | No |
|------------------------------------|-----|----|
| Suitable for Accessible facilities | | x |
| Provision of hot water | x | |

Building code performance clauses

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (c) 5 years if: the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and failure of those building elements to comply with the building code would be easily detected during normal use of the building.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate *sanitation*,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

G12 Water Supplies

G12.3.5

Sanitary fixtures and *sanitary appliances* must be provided with hot water when intended to be used for

- a. utensil washing; and
- b. personal washing, showering, or bathing.