



Raymor Coral Basins

Product Disclosure Information Self-Assessment

Version: V1

| Product name | Raymor Coral Basins |
|--------------------|---------------------|
| Product line | Raymor Basins |
| Product identifier | (7)713114 (7)567890 |

Product description

Raymor Boston Basins are made from vitreous china, with one or three tap hole configuration and a chrome electro-plated plastic overflow ring.

Size: W 500mm, L 450mm, H 185mm

Colour: White

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene - G1.3.2

G12 Water Supplies — G12.3.5

Contributions to compliance

- B2 Durability. B2.3.1 Raymor basins carry a 5-year warranty for normal, domestic use.
- F2 Hazardous building material. F2.3.1 Raymor basins are safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.
- G1 Personal Hygiene. G1.3.2 Raymor basins shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-waterborne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users.

•G12 For Water supplies G12, the prime building product objective is to ensure that the product used in water supply will not contaminate potable water either by way of material leaching into the water or cross connections and will not leak.

Scope of use

Raymor basins are intended for normal, domestic use only. They are designed to enclose water with a separate waste to allow drainage of water. They can be used with water temperatures up to 55 degrees Celsius.

These Raymor basins are to be installed using the waste fitting supplied separately.

They baths are to be mounted on a flat wall surface.

Conditions of use

Raymor basins must be installed in accordance with the instructions provided. We recommend these basins are installed by an authorised installer or plumber. These products are intended for normal, domestic use only. They are cleanable and impervious to moisture — cleaning of these basins shall be done in accordance with the manufacturer's cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

None added

Contact details

| Manufacture location | Overseas |
|--|--|
| Legal and trading name of manufacturer | ARNHOLD & CO LTD |
| Legal and trading name of importer | MICO NEW ZEALAND LIMITED |
| Importer address for service | Unit 3/1 Show Place Christchurch 8024 |
| Importer website | www.mico.co.nz |
| Importer NZBN | 9429040952543 |
| Importer email | info@mico.co.nz |
| Importer phone number | 033381009 |

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Sanitary fixtures and appliances

| | res | NO |
|------------------------------------|-----|----|
| Suitable for Accessible facilities | | × |
| Provision of hot water | × | |

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c) 5 years if:
 - i. the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
 - ii. failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate sanitation,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,

- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

G12 Water Supplies

G12.3.5

Sanitary fixtures and sanitary appliances must be provided with hot water when intended to be used for

- a. utensil washing; and
- b. personal washing, showering, or bathing.