

Class 1

Raymor Dawson II Back to Wall Toilet Suite

Product Disclosure Information Self-Assessment

Version: V1

Product name	Raymor Dawson II Back to Wall Toilet Suite
Product line	Raymor Toilets
Product identifier	(7)741383 (7)741382

Product description

Vitreous china pan and cistern 48mm round dual flush button with chrome finish White soft-close quick release standard seat with metal hinges Rimless design S trap set out 75mm -190mm as standard P trap set out 185mm floor to centre of outlet Optional S trap set out 145mm - 225mm WDI universal inlet valve (bottom right hand or rear left hand entry adjustable

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

Contributions to compliance

- B2 Durability. B2.3.1 Raymor Toilets carry a 5 year warranty for normal, domestic use.
- F2 Hazardous building material. F2.3.1 Raymor basins are safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.
- G1 Personal Hygiene. G1.3.2 Raymor Toilets shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-waterborne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users. G1.2.1. Pans intended for use with flushing cisterns and other flushing devices complying with AS 1172.2. G1.2.2 WELS standard AS/NZS 6400:2016 Water efficient products
- G12 For Water supplies G12, the prime building product objective is to ensure that the product used in water

First party self-assessment generated Aug 22, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=265525f72769b80a74e9dfe6b514793a1fefe38c>Get BPIR Ready | bpir.nz

supply will not contaminate potable water either by way of material leaching into the water or cross connections and will not leak.

Scope of use

The Raymor Dawson II toilet is intended for use in domestic bathrooms. It is suitable for hot and cold-water use, and with mains pressure systems. The unit is floor mounted with either an S trap or P trap configuration. The system is compatible with all fittings manufactured to NZS 3501.

Conditions of use

The Raymor Dawson II suite must be installed by a registered plumber in accordance with the product specification sheet and the NZBC. This product is intended for domestic use only. It can be specified for high use applications such as public amenities, schools, sports facilities, factories, or commercial premises etc. This product is cleanable and impervious to moisture — cleaning shall be done in accordance with the manufacturer's cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

None added

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	XIAMEN BESTBATH CERAMICS CO
Legal and trading name of importer	MICO NEW ZEALAND LIMITED
Importer address for service	Unit 3/1 Show Place Christchurch 8024
Importer website	www.mico.co.nz
Importer NZBN	9429040952543
Importer email	info@mico.co.nz
Importer phone number	033381009

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

First party self-assessment generated Aug 22, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=265525f72769b80a74e9dfe6b514793a1fefe38c>

Get BPIR Ready | bpir.nz

No

Appendix

BPIR Ready selections

Category: Sanitary fixtures and appliances

	Yes	No
Suitable for Accessible facilities		x
Provision of hot water		x

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

(c) 5 years if:

- i. the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
- ii. failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate *sanitation*,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

First party self-assessment generated Aug 22, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=265525f72769b80a74e9dfe6b514793a1fefe38c>

Get BPIR Ready | bpir.nz

First party self-assessment generated Aug 22, 2023 with BPIR Ready.
Source: <https://bpir.nz/form/view?wz=265525f72769b80a74e9dfe6b514793a1fefe38c>

Get BPIR Ready | bpir.nz